

# Trademark/Service Mark Application, Principal Register

Serial Number: 85323341

Filing Date: 05/17/2011

The table below presents the data as entered.

Input Field	Entered
<b>SERIAL NUMBER</b>	85323341
<b>MARK INFORMATION</b>	
<b>*MARK</b>	<a href="\\TICRS\EXPORT11\IMAGEOUT 11\853\233\85323341\xml1\APP0002.JPG">\\TICRS\EXPORT11\IMAGEOUT 11\853\233\85323341\xml1\APP0002.JPG</a>
<b>SPECIAL FORM</b>	YES
<b>USPTO-GENERATED IMAGE</b>	NO
<b>LITERAL ELEMENT</b>	TITAN METAL FABRICATORS
<b>COLOR MARK</b>	NO
<b>*DESCRIPTION OF THE MARK (and Color Location, if applicable)</b>	The mark consists of the word "TITAN" in block lettering above a line, and the words "METAL FABRICATORS" underneath the line.
<b>PIXEL COUNT ACCEPTABLE</b>	NO
<b>PIXEL COUNT</b>	385 x 168
<b>REGISTER</b>	Principal
<b>APPLICANT INFORMATION</b>	
<b>*OWNER OF MARK</b>	Titan Metal Fabricators, Inc.
<b>*STREET</b>	835 Flynn Road
<b>*CITY</b>	Camarillo
<b>*STATE (Required for U.S. applicants)</b>	California

<b>*COUNTRY</b>	United States
<b>*ZIP/POSTAL CODE</b> (Required for U.S. applicants only)	93012
<b>LEGAL ENTITY INFORMATION</b>	
<b>TYPE</b>	corporation
<b>STATE/COUNTRY OF INCORPORATION</b>	California
<b>GOODS AND/OR SERVICES AND BASIS INFORMATION</b>	
<b>INTERNATIONAL CLASS</b>	006
<b>* IDENTIFICATION</b>	corrosion resistant metal process equipment
<b>FILING BASIS</b>	SECTION 1(a)
<b>FIRST USE ANYWHERE DATE</b>	At least as early as 01/00/2011
<b>FIRST USE IN COMMERCE DATE</b>	At least as early as 01/00/2011
<b>SPECIMEN FILE NAME(S)</b>	
<b>ORIGINAL PDF FILE</b>	<a href="#">spec-9631249254-192452939_. Titan Metal Fabricators design mark specification sheet.pdf</a>
<b>CONVERTED PDF FILE(S)</b> (1 page)	<a href="#">\\TICRS\EXPORT11\IMAGEOUT11\853\233\85323341\xml1\APP0003.JPG</a>
<b>SPECIMEN DESCRIPTION</b>	specification sheet
<b>ATTORNEY INFORMATION</b>	
<b>NAME</b>	Jaye G. Heybl
<b>ATTORNEY DOCKET NUMBER</b>	832-47-003
<b>FIRM NAME</b>	KOPPEL, PATRICK, HEYBL & PHILPOTT
<b>STREET</b>	2815 Townsgate Road, Suite 215
<b>CITY</b>	Westlake Village
<b>STATE</b>	California
<b>COUNTRY</b>	United States

<b>ZIP/POSTAL CODE</b>	91361
<b>PHONE</b>	805-373-0060
<b>FAX</b>	805-373-0051
<b>EMAIL ADDRESS</b>	generalmail@koppelpatent.com
<b>AUTHORIZED TO COMMUNICATE VIA EMAIL</b>	Yes
<b>OTHER APPOINTED ATTORNEY</b>	Michael J. Ram; Steven C. Patrick; Brian J. Philpott; Jill R. Heybl; Eric Figueroa; Monica Adjemian
<b>CORRESPONDENCE INFORMATION</b>	
<b>NAME</b>	Jaye G. Heybl
<b>FIRM NAME</b>	KOPPEL, PATRICK, HEYBL & PHILPOTT
<b>STREET</b>	2815 Townsgate Road, Suite 215
<b>CITY</b>	Westlake Village
<b>STATE</b>	California
<b>COUNTRY</b>	United States
<b>ZIP/POSTAL CODE</b>	91361
<b>PHONE</b>	805-373-0060
<b>FAX</b>	805-373-0051
<b>EMAIL ADDRESS</b>	generalmail@koppelpatent.com
<b>AUTHORIZED TO COMMUNICATE VIA EMAIL</b>	Yes
<b>FEE INFORMATION</b>	
<b>NUMBER OF CLASSES</b>	1
<b>FEE PER CLASS</b>	325
<b>*TOTAL FEE DUE</b>	325
<b>*TOTAL FEE PAID</b>	325
<b>SIGNATURE INFORMATION</b>	
<b>SIGNATURE</b>	/Jaye G. Heybl/
<b>SIGNATORY'S</b>	

<b>NAME</b>	Jaye G. Heybl
<b>SIGNATORY'S POSITION</b>	Attorney of record, CA state bar member
<b>DATE SIGNED</b>	05/17/2011

---

## Trademark/Service Mark Application, Principal Register

**Serial Number: 85323341**

**Filing Date: 05/17/2011**

### To the Commissioner for Trademarks:

**MARK:** TITAN METAL FABRICATORS (stylized and/or with design, see [mark](#))

The literal element of the mark consists of TITAN METAL FABRICATORS.

The mark consists of the word "TITAN" in block lettering above a line, and the words "METAL FABRICATORS" underneath the line.

The applicant, Titan Metal Fabricators, Inc., a corporation of California, having an address of  
835 Flynn Road  
Camarillo, California 93012  
United States

requests registration of the trademark/service mark identified above in the United States Patent and Trademark Office on the Principal Register established by the Act of July 5, 1946 (15 U.S.C. Section 1051 et seq.), as amended, for the following:

International Class 006: corrosion resistant metal process equipment

In International Class 006, the mark was first used at least as early as 01/00/2011, and first used in commerce at least as early as 01/00/2011, and is now in use in such commerce. The applicant is submitting one specimen(s) showing the mark as used in commerce on or in connection with any item in the class of listed goods and/or services, consisting of a(n) specification sheet.

#### Original PDF file:

[spec-9631249254-192452939 . Titan Metal Fabricators design mark specification sheet.pdf](#)

Converted PDF file(s) (1 page)

[Specimen File 1](#)

The applicant's current Attorney Information:

Jaye G. Heybl and Michael J. Ram; Steven C. Patrick; Brian J. Philpott; Jill R. Heybl; Eric Figueroa;  
Monica Adjemian of KOPPEL, PATRICK, HEYBL & PHILPOTT  
2815 Townsgate Road, Suite 215  
Westlake Village, California 91361  
United States

The attorney docket/reference number is 832-47-003.

The applicant's current Correspondence Information:

Jaye G. Heybl

KOPPEL, PATRICK, HEYBL & PHILPOTT

2815 Townsgate Road, Suite 215

Westlake Village, California 91361

805-373-0060(phone)

805-373-0051(fax)

generalmail@koppelpatent.com (authorized)

A fee payment in the amount of \$325 has been submitted with the application, representing payment for 1 class(es).

### **Declaration**

The undersigned, being hereby warned that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. Section 1001, and that such willful false statements, and the like, may jeopardize the validity of the application or any resulting registration, declares that he/she is properly authorized to execute this application on behalf of the applicant; he/she believes the applicant to be the owner of the trademark/service mark sought to be registered, or, if the application is being filed under 15 U.S.C. Section 1051(b), he/she believes applicant to be entitled to use such mark in commerce; to the best of his/her knowledge and belief no other person, firm, corporation, or association has the right to use the mark in commerce, either in the identical form thereof or in such near resemblance thereto as to be likely, when used on or in connection with the goods/services of such other person, to cause confusion, or to cause mistake, or to deceive; and that all statements made of his/her own knowledge are true; and that all statements made on information and belief are believed to be true.

Signature: /Jaye G. Heybl/ Date Signed: 05/17/2011

Signatory's Name: Jaye G. Heybl

Signatory's Position: Attorney of record, CA state bar member

RAM Sale Number: 5608

RAM Accounting Date: 05/18/2011

Serial Number: 85323341

Internet Transmission Date: Tue May 17 19:31:21 EDT 2011

TEAS Stamp: USPTO/BAS-96.31.249.254-2011051719312154

4823-85323341-480a5de3ce8ad6be2505322297

1b6b6da8-DA-5608-20110517192452939594

**TITAN**

---

**METAL FABRICATORS**

# TITAN

## METAL FABRICATORS

ITEM	QTY	EQUIPMENT DESCRIPTION																																																		
1	1	<b>Alloy C-276 Shell &amp; Tube Heat Exchanger</b> TITAN Model Number: HCCS-XXX-XX-X-XXX-BEMH																																																		
<b>THERMAL DESIGN INFORMATION</b>																																																				
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th colspan="2" style="text-align: center;">SHELLSIDE</th> <th colspan="2" style="text-align: center;">TUBESIDE</th> </tr> <tr> <th style="text-align: left;">Fluid Name:</th> <td colspan="2" style="text-align: center;">Shell Side Fluid Name</td> <td colspan="2" style="text-align: center;">Tube Side Fluid Name</td> </tr> <tr> <td></td> <th style="text-align: center;">IN</th> <th style="text-align: center;">OUT</th> <th style="text-align: center;">IN</th> <th style="text-align: center;">OUT</th> </tr> </thead> <tbody> <tr> <td style="text-align: left;">Fluid Quantity (kg/h):</td> <td style="text-align: center;">50,000</td> <td style="text-align: center;">50,000</td> <td style="text-align: center;">15,000</td> <td style="text-align: center;">15,000</td> </tr> <tr> <td style="text-align: left;">Temperature(C):</td> <td style="text-align: center;">120</td> <td style="text-align: center;">120</td> <td style="text-align: center;">50</td> <td style="text-align: center;">75</td> </tr> <tr> <td style="text-align: left;">Density (kg/m<sup>3</sup>):</td> <td style="text-align: center;">0.954</td> <td style="text-align: center;">0.954</td> <td style="text-align: center;">0.875</td> <td style="text-align: center;">0.875</td> </tr> <tr> <td style="text-align: left;">Viscosity (cp):</td> <td style="text-align: center;">0.0150</td> <td style="text-align: center;">0.0175</td> <td style="text-align: center;">0.0091</td> <td style="text-align: center;">0.0095</td> </tr> <tr> <td style="text-align: left;">Specific Heat (Kj/(kg*K)):</td> <td style="text-align: center;">0.5692</td> <td style="text-align: center;">1.0247</td> <td style="text-align: center;">0.3909</td> <td style="text-align: center;">0.4324</td> </tr> <tr> <td style="text-align: left;">Thermal Cond. (W/(m*K)):</td> <td style="text-align: center;">0.018</td> <td style="text-align: center;">0.396</td> <td style="text-align: center;">0.063</td> <td style="text-align: center;">0.110</td> </tr> <tr> <td style="text-align: left;">Pressure (bar):</td> <td style="text-align: center;">50.1</td> <td style="text-align: center;">49.5</td> <td style="text-align: center;">50.1</td> <td style="text-align: center;">49.5</td> </tr> </tbody> </table>		SHELLSIDE		TUBESIDE		Fluid Name:	Shell Side Fluid Name		Tube Side Fluid Name			IN	OUT	IN	OUT	Fluid Quantity (kg/h):	50,000	50,000	15,000	15,000	Temperature(C):	120	120	50	75	Density (kg/m <sup>3</sup> ):	0.954	0.954	0.875	0.875	Viscosity (cp):	0.0150	0.0175	0.0091	0.0095	Specific Heat (Kj/(kg*K)):	0.5692	1.0247	0.3909	0.4324	Thermal Cond. (W/(m*K)):	0.018	0.396	0.063	0.110	Pressure (bar):	50.1	49.5	50.1	49.5
	SHELLSIDE		TUBESIDE																																																	
Fluid Name:	Shell Side Fluid Name		Tube Side Fluid Name																																																	
	IN	OUT	IN	OUT																																																
Fluid Quantity (kg/h):	50,000	50,000	15,000	15,000																																																
Temperature(C):	120	120	50	75																																																
Density (kg/m <sup>3</sup> ):	0.954	0.954	0.875	0.875																																																
Viscosity (cp):	0.0150	0.0175	0.0091	0.0095																																																
Specific Heat (Kj/(kg*K)):	0.5692	1.0247	0.3909	0.4324																																																
Thermal Cond. (W/(m*K)):	0.018	0.396	0.063	0.110																																																
Pressure (bar):	50.1	49.5	50.1	49.5																																																
<b>MECHANICAL DESIGN INFORMATION</b>																																																				
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="text-align: left;">Design Pressure (bar):</td> <td style="text-align: center;">full vacuum / 4</td> <td style="text-align: center;">full vacuum / 150</td> </tr> <tr> <td style="text-align: left;">Design Temperature (C):</td> <td style="text-align: center;">-28 / 175</td> <td style="text-align: center;">-20 / 350</td> </tr> <tr> <td style="text-align: left;"># Passes per Shell:</td> <td style="text-align: center;">1</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="text-align: left;">Corrosion Allowance (mm):</td> <td style="text-align: center;">1.588</td> <td style="text-align: center;">0.000</td> </tr> <tr> <td style="text-align: left;">Inlet Nozzle:</td> <td style="text-align: center;">DN250 PN16 RFSO</td> <td style="text-align: center;">DN100 PN16 Lap Joint</td> </tr> <tr> <td style="text-align: left;">Outlet Nozzle:</td> <td style="text-align: center;">DN250 PN16 RFSO</td> <td style="text-align: center;">DN100 PN16 Lap Joint</td> </tr> <tr> <td style="text-align: left;">Additional Nozzle:</td> <td style="text-align: center;">(2) ¾" 3000# coupling</td> <td style="text-align: center;">N/A</td> </tr> </tbody> </table>	Design Pressure (bar):	full vacuum / 4	full vacuum / 150	Design Temperature (C):	-28 / 175	-20 / 350	# Passes per Shell:	1	1	Corrosion Allowance (mm):	1.588	0.000	Inlet Nozzle:	DN250 PN16 RFSO	DN100 PN16 Lap Joint	Outlet Nozzle:	DN250 PN16 RFSO	DN100 PN16 Lap Joint	Additional Nozzle:	(2) ¾" 3000# coupling	N/A																													
Design Pressure (bar):	full vacuum / 4	full vacuum / 150																																																		
Design Temperature (C):	-28 / 175	-20 / 350																																																		
# Passes per Shell:	1	1																																																		
Corrosion Allowance (mm):	1.588	0.000																																																		
Inlet Nozzle:	DN250 PN16 RFSO	DN100 PN16 Lap Joint																																																		
Outlet Nozzle:	DN250 PN16 RFSO	DN100 PN16 Lap Joint																																																		
Additional Nozzle:	(2) ¾" 3000# coupling	N/A																																																		
<b>DIMENSIONS / MATERIALS OF CONSTRUCTION</b>																																																				
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="text-align: left;">Tubes:</td> <td colspan="2" style="text-align: center;">(415) 19.5mm OD X 0.889mm Average Wall X 6096mm Long Alloy C-276 Welded (SB-622)</td> </tr> <tr> <td style="text-align: left;">Shell:</td> <td colspan="2" style="text-align: center;">Carbon Steel (SA-106B)</td> </tr> <tr> <td style="text-align: left;">Expansion Joint:</td> <td colspan="2" style="text-align: center;">Bellows Type, SA-106B stubs with Inconel 625 Bellows</td> </tr> <tr> <td style="text-align: left;">Shell-Side Nozzles:</td> <td colspan="2" style="text-align: center;">Carbon Steel (SA-106B / SA105)</td> </tr> <tr> <td style="text-align: left;">Shell-Side Gaskets:</td> <td colspan="2" style="text-align: center;">Ring Type Gylon 3545</td> </tr> <tr> <td style="text-align: left;">Baffle Cage:</td> <td colspan="2" style="text-align: center;">Carbon Steel</td> </tr> <tr> <td style="text-align: left;">Tubesheets:</td> <td colspan="2" style="text-align: center;">Alloy C-276 loose lined Carbon Steel (SB-575 / SA-516-70)</td> </tr> <tr> <td style="text-align: left;">Bonnetts:</td> <td colspan="2" style="text-align: center;">Alloy C-276 Channel Section with 2:1 Elliptical Heads (SB-575)</td> </tr> <tr> <td style="text-align: left;">Bonnet Nozzles:</td> <td colspan="2" style="text-align: center;">Alloy C-276 with Carbon Steel Lap Flanges (SB-619 / SA105)</td> </tr> <tr> <td style="text-align: left;">Tube-Side Gaskets:</td> <td colspan="2" style="text-align: center;">Ring Type 25% Glass Filled PTFE</td> </tr> </tbody> </table>	Tubes:	(415) 19.5mm OD X 0.889mm Average Wall X 6096mm Long Alloy C-276 Welded (SB-622)		Shell:	Carbon Steel (SA-106B)		Expansion Joint:	Bellows Type, SA-106B stubs with Inconel 625 Bellows		Shell-Side Nozzles:	Carbon Steel (SA-106B / SA105)		Shell-Side Gaskets:	Ring Type Gylon 3545		Baffle Cage:	Carbon Steel		Tubesheets:	Alloy C-276 loose lined Carbon Steel (SB-575 / SA-516-70)		Bonnetts:	Alloy C-276 Channel Section with 2:1 Elliptical Heads (SB-575)		Bonnet Nozzles:	Alloy C-276 with Carbon Steel Lap Flanges (SB-619 / SA105)		Tube-Side Gaskets:	Ring Type 25% Glass Filled PTFE																					
Tubes:	(415) 19.5mm OD X 0.889mm Average Wall X 6096mm Long Alloy C-276 Welded (SB-622)																																																			
Shell:	Carbon Steel (SA-106B)																																																			
Expansion Joint:	Bellows Type, SA-106B stubs with Inconel 625 Bellows																																																			
Shell-Side Nozzles:	Carbon Steel (SA-106B / SA105)																																																			
Shell-Side Gaskets:	Ring Type Gylon 3545																																																			
Baffle Cage:	Carbon Steel																																																			
Tubesheets:	Alloy C-276 loose lined Carbon Steel (SB-575 / SA-516-70)																																																			
Bonnetts:	Alloy C-276 Channel Section with 2:1 Elliptical Heads (SB-575)																																																			
Bonnet Nozzles:	Alloy C-276 with Carbon Steel Lap Flanges (SB-619 / SA105)																																																			
Tube-Side Gaskets:	Ring Type 25% Glass Filled PTFE																																																			
<b>DESIGN ADDITIONAL REQUIREMENTS</b>																																																				
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="text-align: left;">Code:</td> <td colspan="2" style="text-align: center;">ASME Code Section VIII Div. 1, Stamped PED Where Applicable, CE Stamped</td> </tr> <tr> <td style="text-align: left;">Design Standards:</td> <td colspan="2" style="text-align: center;">TEMA 9<sup>th</sup> Edition, Type: BEM, Class: B</td> </tr> <tr> <td style="text-align: left;">External Surface Finish:</td> <td colspan="2" style="text-align: center;">All exposed carbon steel will be painted with epoxy paint, Thermaline 450, Color Red. All exposed Alloy surfaces will be blasted to a uniform matte finish.</td> </tr> <tr> <td style="text-align: left;">Internal Surface Finish:</td> <td colspan="2" style="text-align: center;">Mill</td> </tr> </tbody> </table>	Code:	ASME Code Section VIII Div. 1, Stamped PED Where Applicable, CE Stamped		Design Standards:	TEMA 9 <sup>th</sup> Edition, Type: BEM, Class: B		External Surface Finish:	All exposed carbon steel will be painted with epoxy paint, Thermaline 450, Color Red. All exposed Alloy surfaces will be blasted to a uniform matte finish.		Internal Surface Finish:	Mill																																							
Code:	ASME Code Section VIII Div. 1, Stamped PED Where Applicable, CE Stamped																																																			
Design Standards:	TEMA 9 <sup>th</sup> Edition, Type: BEM, Class: B																																																			
External Surface Finish:	All exposed carbon steel will be painted with epoxy paint, Thermaline 450, Color Red. All exposed Alloy surfaces will be blasted to a uniform matte finish.																																																			
Internal Surface Finish:	Mill																																																			
<b>PRICE:</b>	<b>\$ .00 USD ea.</b>																																																			
<b>DELIVERY:</b>	<b>* - * Weeks after receipt of approved drawings</b>																																																			

**TITAN**

---

**METAL FABRICATORS**

# TITAN

## METAL FABRICATORS

ITEM	QTY	EQUIPMENT DESCRIPTION																																																		
1	1	<b>Alloy C-276 Shell &amp; Tube Heat Exchanger</b> TITAN Model Number: HCCS-XXX-XX-X-XXX-BEMH																																																		
<b>THERMAL DESIGN INFORMATION</b>																																																				
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th colspan="2" style="text-align: center;">SHELLSIDE</th> <th colspan="2" style="text-align: center;">TUBESIDE</th> </tr> <tr> <th style="text-align: left;">Fluid Name:</th> <td colspan="2" style="text-align: center;">Shell Side Fluid Name</td> <td colspan="2" style="text-align: center;">Tube Side Fluid Name</td> </tr> <tr> <td></td> <th style="text-align: center;">IN</th> <th style="text-align: center;">OUT</th> <th style="text-align: center;">IN</th> <th style="text-align: center;">OUT</th> </tr> </thead> <tbody> <tr> <td style="text-align: left;">Fluid Quantity (kg/h):</td> <td style="text-align: center;">50,000</td> <td style="text-align: center;">50,000</td> <td style="text-align: center;">15,000</td> <td style="text-align: center;">15,000</td> </tr> <tr> <td style="text-align: left;">Temperature(C):</td> <td style="text-align: center;">120</td> <td style="text-align: center;">120</td> <td style="text-align: center;">50</td> <td style="text-align: center;">75</td> </tr> <tr> <td style="text-align: left;">Density (kg/m<sup>3</sup>):</td> <td style="text-align: center;">0.954</td> <td style="text-align: center;">0.954</td> <td style="text-align: center;">0.875</td> <td style="text-align: center;">0.875</td> </tr> <tr> <td style="text-align: left;">Viscosity (cp):</td> <td style="text-align: center;">0.0150</td> <td style="text-align: center;">0.0175</td> <td style="text-align: center;">0.0091</td> <td style="text-align: center;">0.0095</td> </tr> <tr> <td style="text-align: left;">Specific Heat (Kj/(kg*K)):</td> <td style="text-align: center;">0.5692</td> <td style="text-align: center;">1.0247</td> <td style="text-align: center;">0.3909</td> <td style="text-align: center;">0.4324</td> </tr> <tr> <td style="text-align: left;">Thermal Cond. (W/(m*K)):</td> <td style="text-align: center;">0.018</td> <td style="text-align: center;">0.396</td> <td style="text-align: center;">0.063</td> <td style="text-align: center;">0.110</td> </tr> <tr> <td style="text-align: left;">Pressure (bar):</td> <td style="text-align: center;">50.1</td> <td style="text-align: center;">49.5</td> <td style="text-align: center;">50.1</td> <td style="text-align: center;">49.5</td> </tr> </tbody> </table>		SHELLSIDE		TUBESIDE		Fluid Name:	Shell Side Fluid Name		Tube Side Fluid Name			IN	OUT	IN	OUT	Fluid Quantity (kg/h):	50,000	50,000	15,000	15,000	Temperature(C):	120	120	50	75	Density (kg/m <sup>3</sup> ):	0.954	0.954	0.875	0.875	Viscosity (cp):	0.0150	0.0175	0.0091	0.0095	Specific Heat (Kj/(kg*K)):	0.5692	1.0247	0.3909	0.4324	Thermal Cond. (W/(m*K)):	0.018	0.396	0.063	0.110	Pressure (bar):	50.1	49.5	50.1	49.5
	SHELLSIDE		TUBESIDE																																																	
Fluid Name:	Shell Side Fluid Name		Tube Side Fluid Name																																																	
	IN	OUT	IN	OUT																																																
Fluid Quantity (kg/h):	50,000	50,000	15,000	15,000																																																
Temperature(C):	120	120	50	75																																																
Density (kg/m <sup>3</sup> ):	0.954	0.954	0.875	0.875																																																
Viscosity (cp):	0.0150	0.0175	0.0091	0.0095																																																
Specific Heat (Kj/(kg*K)):	0.5692	1.0247	0.3909	0.4324																																																
Thermal Cond. (W/(m*K)):	0.018	0.396	0.063	0.110																																																
Pressure (bar):	50.1	49.5	50.1	49.5																																																
<b>MECHANICAL DESIGN INFORMATION</b>																																																				
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="text-align: left;">Design Pressure (bar):</td> <td style="text-align: center;">full vacuum / 4</td> <td style="text-align: center;">full vacuum / 150</td> </tr> <tr> <td style="text-align: left;">Design Temperature (C):</td> <td style="text-align: center;">-28 / 175</td> <td style="text-align: center;">-20 / 350</td> </tr> <tr> <td style="text-align: left;"># Passes per Shell:</td> <td style="text-align: center;">1</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="text-align: left;">Corrosion Allowance (mm):</td> <td style="text-align: center;">1.588</td> <td style="text-align: center;">0.000</td> </tr> <tr> <td style="text-align: left;">Inlet Nozzle:</td> <td style="text-align: center;">DN250 PN16 RFSO</td> <td style="text-align: center;">DN100 PN16 Lap Joint</td> </tr> <tr> <td style="text-align: left;">Outlet Nozzle:</td> <td style="text-align: center;">DN250 PN16 RFSO</td> <td style="text-align: center;">DN100 PN16 Lap Joint</td> </tr> <tr> <td style="text-align: left;">Additional Nozzle:</td> <td style="text-align: center;">(2) ¾" 3000# coupling</td> <td style="text-align: center;">N/A</td> </tr> </tbody> </table>	Design Pressure (bar):	full vacuum / 4	full vacuum / 150	Design Temperature (C):	-28 / 175	-20 / 350	# Passes per Shell:	1	1	Corrosion Allowance (mm):	1.588	0.000	Inlet Nozzle:	DN250 PN16 RFSO	DN100 PN16 Lap Joint	Outlet Nozzle:	DN250 PN16 RFSO	DN100 PN16 Lap Joint	Additional Nozzle:	(2) ¾" 3000# coupling	N/A																													
Design Pressure (bar):	full vacuum / 4	full vacuum / 150																																																		
Design Temperature (C):	-28 / 175	-20 / 350																																																		
# Passes per Shell:	1	1																																																		
Corrosion Allowance (mm):	1.588	0.000																																																		
Inlet Nozzle:	DN250 PN16 RFSO	DN100 PN16 Lap Joint																																																		
Outlet Nozzle:	DN250 PN16 RFSO	DN100 PN16 Lap Joint																																																		
Additional Nozzle:	(2) ¾" 3000# coupling	N/A																																																		
<b>DIMENSIONS / MATERIALS OF CONSTRUCTION</b>																																																				
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="text-align: left;">Tubes:</td> <td colspan="2" style="text-align: center;">(415) 19.5mm OD X 0.889mm Average Wall X 6096mm Long Alloy C-276 Welded (SB-622)</td> </tr> <tr> <td style="text-align: left;">Shell:</td> <td colspan="2" style="text-align: center;">Carbon Steel (SA-106B)</td> </tr> <tr> <td style="text-align: left;">Expansion Joint:</td> <td colspan="2" style="text-align: center;">Bellows Type, SA-106B stubs with Inconel 625 Bellows</td> </tr> <tr> <td style="text-align: left;">Shell-Side Nozzles:</td> <td colspan="2" style="text-align: center;">Carbon Steel (SA-106B / SA105)</td> </tr> <tr> <td style="text-align: left;">Shell-Side Gaskets:</td> <td colspan="2" style="text-align: center;">Ring Type Gylon 3545</td> </tr> <tr> <td style="text-align: left;">Baffle Cage:</td> <td colspan="2" style="text-align: center;">Carbon Steel</td> </tr> <tr> <td style="text-align: left;">Tubesheets:</td> <td colspan="2" style="text-align: center;">Alloy C-276 loose lined Carbon Steel (SB-575 / SA-516-70)</td> </tr> <tr> <td style="text-align: left;">Bonnetts:</td> <td colspan="2" style="text-align: center;">Alloy C-276 Channel Section with 2:1 Elliptical Heads (SB-575)</td> </tr> <tr> <td style="text-align: left;">Bonnet Nozzles:</td> <td colspan="2" style="text-align: center;">Alloy C-276 with Carbon Steel Lap Flanges (SB-619 / SA105)</td> </tr> <tr> <td style="text-align: left;">Tube-Side Gaskets:</td> <td colspan="2" style="text-align: center;">Ring Type 25% Glass Filled PTFE</td> </tr> </tbody> </table>	Tubes:	(415) 19.5mm OD X 0.889mm Average Wall X 6096mm Long Alloy C-276 Welded (SB-622)		Shell:	Carbon Steel (SA-106B)		Expansion Joint:	Bellows Type, SA-106B stubs with Inconel 625 Bellows		Shell-Side Nozzles:	Carbon Steel (SA-106B / SA105)		Shell-Side Gaskets:	Ring Type Gylon 3545		Baffle Cage:	Carbon Steel		Tubesheets:	Alloy C-276 loose lined Carbon Steel (SB-575 / SA-516-70)		Bonnetts:	Alloy C-276 Channel Section with 2:1 Elliptical Heads (SB-575)		Bonnet Nozzles:	Alloy C-276 with Carbon Steel Lap Flanges (SB-619 / SA105)		Tube-Side Gaskets:	Ring Type 25% Glass Filled PTFE																					
Tubes:	(415) 19.5mm OD X 0.889mm Average Wall X 6096mm Long Alloy C-276 Welded (SB-622)																																																			
Shell:	Carbon Steel (SA-106B)																																																			
Expansion Joint:	Bellows Type, SA-106B stubs with Inconel 625 Bellows																																																			
Shell-Side Nozzles:	Carbon Steel (SA-106B / SA105)																																																			
Shell-Side Gaskets:	Ring Type Gylon 3545																																																			
Baffle Cage:	Carbon Steel																																																			
Tubesheets:	Alloy C-276 loose lined Carbon Steel (SB-575 / SA-516-70)																																																			
Bonnetts:	Alloy C-276 Channel Section with 2:1 Elliptical Heads (SB-575)																																																			
Bonnet Nozzles:	Alloy C-276 with Carbon Steel Lap Flanges (SB-619 / SA105)																																																			
Tube-Side Gaskets:	Ring Type 25% Glass Filled PTFE																																																			
<b>DESIGN ADDITIONAL REQUIREMENTS</b>																																																				
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="text-align: left;">Code:</td> <td colspan="2" style="text-align: center;">ASME Code Section VIII Div. 1, Stamped PED Where Applicable, CE Stamped</td> </tr> <tr> <td style="text-align: left;">Design Standards:</td> <td colspan="2" style="text-align: center;">TEMA 9<sup>th</sup> Edition, Type: BEM, Class: B</td> </tr> <tr> <td style="text-align: left;">External Surface Finish:</td> <td colspan="2" style="text-align: center;">All exposed carbon steel will be painted with epoxy paint, Thermaline 450, Color Red. All exposed Alloy surfaces will be blasted to a uniform matte finish.</td> </tr> <tr> <td style="text-align: left;">Internal Surface Finish:</td> <td colspan="2" style="text-align: center;">Mill</td> </tr> </tbody> </table>	Code:	ASME Code Section VIII Div. 1, Stamped PED Where Applicable, CE Stamped		Design Standards:	TEMA 9 <sup>th</sup> Edition, Type: BEM, Class: B		External Surface Finish:	All exposed carbon steel will be painted with epoxy paint, Thermaline 450, Color Red. All exposed Alloy surfaces will be blasted to a uniform matte finish.		Internal Surface Finish:	Mill																																							
Code:	ASME Code Section VIII Div. 1, Stamped PED Where Applicable, CE Stamped																																																			
Design Standards:	TEMA 9 <sup>th</sup> Edition, Type: BEM, Class: B																																																			
External Surface Finish:	All exposed carbon steel will be painted with epoxy paint, Thermaline 450, Color Red. All exposed Alloy surfaces will be blasted to a uniform matte finish.																																																			
Internal Surface Finish:	Mill																																																			
<b>PRICE:</b>	<b>\$ .00 USD ea.</b>																																																			
<b>DELIVERY:</b>	<b>* - * Weeks after receipt of approved drawings</b>																																																			